

## Section VII. Technical Specifications

Item	Specification	Statement of Compliance
		<p><i>[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.] Please state the brand and model being offered</i></p>
<b>IT EQUIPMENT, SUPPLIES, MATERIALS AND ACCESSORIES</b>		
1	UPS-Smart-UPS Lithium Ion, Short Depth 1000VA, 230V with SmartConnect, Output power capacity: 800Watts / 1000VA, Rack Height: 2U, Output Connections: (6) IEC 60320 C13 (Battery Backup), Nominal Output Voltage: 230V, Nominal Input Voltage: 230V, Input Connections: IEC 60320 C14	
2	UPS -Smart-UPS C Lithium Ion, Short Depth 500VA, 230V with SmartConnect, Output power capacity: 400 Watts / 500VA, Rack Height: 1U, Output Connections: (4) IEC 60320 C13 (Battery Backup), Nominal Output Voltage: 230V, Nominal Input Voltage: 230V, Input Connections: IEC 60320 C14	
3	Network Switch 8 port; ,10/100/1000 mbps switched ports D-Link DGS-108, 8-Port Gigabit Unmanaged Desktop Metal Switch, 802.3 ethernet or 802.3u fast Ethernet, or 802.3ab gigabit Ethernet	
4	KVM Switch 4 Ports USB2.0/3.0 Switch Selector VGA Print Auto Switch Monitor Box VGA Splitter; 4 Ports USB2.0 KVM Switch	



	Selector VGA Print Auto Switch Monitor Box VGA Splitter KVM Switch	
5	Laptop, branded and brand new ; Intel Core i5-10210U, 15.6" HD Display, 8GB RAM or higher, 256GB PCIe NVMe SSD, 1TB 5400 RPM HDD, 2GB-GDDR5 Graphics	
6	Projector, branded and brand new; EB-X41 XGA 3600 ANSI Lumens, XGA, up to 10,000 Hours Lamp Life, Optical Zoom, 30-300 inches lage size, Wireless LAN, HDMI, VGA, USB 2.0 Type A, B	
7	Printer, branded and brand new; Wi-Fi Duplex All-in-One Ink Tank Printer with ADF	
8	Drill: 36V Li-Ion Cordless Hammer Drill (SET)	
9	Power supply; HP460W 466249-001 HSTNS-PL14 511777-001	
10	HDD 1TB Black (WD1003FZEX) SATA 6Gb/s 3.5-inch HDD	
11	HDD SCSCI Lenovo 00WG696 900GB 10k SAS 12G 2.5"	
12	STEL6000300 6TB Backup-Plus Desktop	
13	Hot Air Rework Station 2 in 1 YiHua 8786D-I Power Consumption 700 W Air Flow Type Brushless Fan Max Air Flow Volume 120L/min Hot Air Gun 650 W Temperature Range 100°C ~ 480°C	
14	Network Tester: Fluke Network Cable Tester RJ11, RJ45, MICROMAPPER; Equipment Type: Cable Tester, Connector Type: RJ11, RJ45, Tone: Yes, Power Source: Battery, Battery Type: AAA, Battery Life: 20 h, Weight: 130g, Display Type: LED, Height: 32mm, Length: 141mm, Maximum Operating Temperature: +40°C, Minimum Operating Temperature: 0°C, Width: 75mm	
15	Punch tool; With 110 and Krone Blade, TC-PDT, Insert & Cut Terminations in one Operation, Precision Blades are Interchangeable & Reversible, Network Punch Tool, 110 Punch Down Tool	
16	POE-Gigabit 24V-24W Adapter - 24V, 1A	
17	LOOP ALLOY Power Distribution Unit (PDU) Power Strip Unit 8	
18	HDMI Splitter 1 In 4 Out 4K 3D Support Signal Amplification	
19	Anti-static wrist band: Electrostatic Discharge Anti-Static Wrist Strap Ground Wire Mat Set: 30*40cm/11.81*15.74" Mat Thickness: Approx. 2mm/0.07 (imm error) Mat Temperature Resistance: 380°C Wrist Strap Material: PVC Cable Size: 2mm*1.8m/0.07*70.86	

Go

