Section VII. Technical Specifications

Item	Specification	Statement of Compliance				
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's unamended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]Please state the brand and model being offered				
IT EQU	UPS-Smart-UPS Lithium Ion, Short Depth 1000VA, 230V with SmartConnect, Output power capacity: 800Watts / 1000VA, Rack Height: 2U, Output Connections: (6) IEC 60320 C13 (Battery Backup), Nominal Output Voltage: 230V, Nominal Input Voltage: 230V, Input Connections: IEC 60320 C14	CCESSORIES				
2	UPS -Smart-UPS C Lithium Ion, Short Depth 500VA, 230V with SmartConnect, Output power capacity: 400 Watts / 500VA, Rack Height: 1U, Output Connections: (4) IEC 60320 C13 (Battery Backup), Nominal Output Voltage: 230V, Nominal Input Voltage: 230V, Input Connections: IEC 60320 C14					
3	Network Switch 8 port; ,10/100/1000 mbps switched ports D-Link DGS-108, 8-Port Gigabit Unmanaged Desktop Metal Switch, 802.3 ethernet or 802.3u fast Ethernet, or 802.3ab gigabit Ethernet					
4	KVM Switch 4 Ports USB2.0/3.0 Switch Selector VGA Print Auto Switch Monitor Box VGA Splitter; 4 Ports USB2.0 KVM Switch					



	Selector VGA Print Auto Switch Monitor Box VGA Splitter KVM Switch	
5	Laptop; Intel Core i5-10210U, 15.6" HD Display, 8GB RAM or higher, 256GB PCIe NVMe SSD, 1TB 5400 RPM HDD, 2GB- GDDR5 Graphics	
6	Projector; EB-X41 XGA 3600 ANSI Lumens, XGA, up to 10,000 Hours Lamp Life, Optical Zoom, 30-300 inches lage size, Wireless LAN, HDMI, VGA, USB 2.0 Type A, B	
7	Printer, Wi-Fi Duplex All-in-One Ink Tank Printer with ADF	
8	Drill: 36V Li-Ion Cordless Hammer Drill (SET)	
9	Power supply; HP460W 466249-001 HSTNS- PL14 511777-001	
10	HDD 1TB Black (WD1003FZEX) SATA 6Gb/s 3.5-inch HDD	
11	HDD SCSCI Lenovo 00WG696 900GB 10k SAS 12G 2.5"	
12	STEL6000300 6TB Backup-Plus Desktop	
13	Hot Air Rework Station 2 in 1 YiHua 8786D-	
	I Power Consumption 700 W Air Flow Type	
	Brushless Fan Max Air Flow Volume	
	120L/min Hot Air Gun 650 W Temperature	
	Range 100°C ~ 480°C	
14	Network Tester: Fluke Network Cable Tester	
	RJ11, RJ45, MICROMAPPER; Equipment	
	Type: Cable Tester, Connector Type: RJ11,	
	RJ45, Tone: Yes, Power Source: Battery,	
	Battery Type: AAA, Battery Life: 20 h,	
	Weight: 130g, Display Type: LED, Height:	
	32mm, Length: 141mm, Maximum Operating	
	Temperature: +40°C, Minimum Operating	
	Temperature: 0°C, Width: 75mm	
15	Punch tool; With 110 and Krone Blade, TC-	
	PDT, Insert & Cut Terminations in one	
	Operation, Precision Blades are	
	Interchangeable & Reversible, Network	
	Punch Tool, 110 Punch Down Tool	
16	POE-Gigabit 24V-24W Adapter - 24V, 1A	
17	LOOP ALLOY Power Distribution Unit	
	(PDU) Power Strip Unit 8	
18	HDMI Splitter 1 In 4 Out 4K 3D Support	
	Signal Amplification	
19	Anti-static wrist band: Electrostatic Discharge	
	Anti-Static Wrist Strap Ground Wire Mat Set:	
	30*40cm/11.81*15.74" Mat Thickness:	
	Approx. 2mm/0.07 (imm error) Mat	
	Temperature Resistance: 380°C Wrist Strap	
	Material: PVC Cable Size:	
	2mm*1.8m/0.07*70.86	
20	Aluminum Ladder Size:16ft, Weight 13.9kg;	
	Dimensions: (WxHxD cm) Closed	
	63x123x25, Open A Position: 63x244x140	

21	External Drive 1TB USB 3.2; Portable 1TB						
	USB 3.2 Type C						
22	Microsoft Office, Microsoft Office						
	Professional Plus 2016 Product Key for 1 PC,						
	Lifetime						
23	UTP Cat6 Unshielded AWG24 Gray Data						
	LAN 1000 feet						
24	Electrical Tape 6pcs per pack						
25	Expansion Bolt 5/8" Stainless Dyna Bolt /						
	Expansion Bolt						
26	Keyboard Brush complete set 19 in 1 Anti-						
	Static Brush						
27	Rubber Boots: RJ45 Cat6 Cat5 Network						
	Rubber Boots Set of 100pcs						
28	Thermal Paste						
	LOT EVALUATION						

I he	reby	certi	fy that th	e statement	of	compli	ian	ce t	o the f	foregoin	g tec	hnical speci	fica	ations
are	true	and	correct,	otherwise,	if	found	to	be	false	during	bid	evaluation	or	post-
qua	lifica	tion,	the same	shall give r	ise	to auto	oma	atic	disqu	alificati	on o	f our bid.		

Name of Company	Signature over Printed Name of	Date
	Authorized Representative	

