

Section III. Bid Data Sheet

GP

Section III- BID DATA SHEET – PROCUREMENT OF ELECTRICAL/ELECTRONICS EQUIPMENT

=====

ITB Clause				
5.3	<p>For this purpose, contracts similar to the Project shall be:</p> <p><i>a. Delivery of Electrical and Electronics Equipment</i></p> <p><i>b. completed within two (2) years (July 2019 to July 2021) prior to the deadline for the submission and receipt of bids.</i></p>			
7.1	SUBCONTRACTING IS NOT ALLOWED			
12	The price of the Goods shall be quoted DDP , CSU, Virac, Catanduanes or the applicable International Commercial Terms (INCOTERMS) for this Project.			
14.1	<p>The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts:</p> <p><i>a. The amount of not less than <u>Php2,019.60</u> (2% of the ABC), if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or</i></p> <p><i>b. The amount of not less than <u>Php5,049.00</u> (5% of ABC), if bid security is in Surety Bond.</i></p>			
15	<p>Each bidder shall submit one copy of the first and second components of its Bid.</p> <p>The Procuring Entity allows the submission of bids through online submission or any other electronic means, hence, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.</p>			
19.2	Partial bid is allowed			
19.3	List each items indicating quantity and ABC			
	Unit of Measure	Brief Description	QTY	ABC/UNIT
	unit	<p>TRUE RMS AC/DC CLAMP METER Features and benefits</p> <p>iFlex flexible current probe (sold separately) expands the measurement range to 2500 A AC while providing increased display flexibility, ability to measure awkward sized conductors and improved wire access</p> <p>CAT IV 600 V, CAT III 1000 V</p> <p>Proprietary inrush measurement technology to filter out noise and capture motor starting current exactly as the circuit protection sees it</p> <p>Ergonomic design fits in your hand and can be used while wearing personal protective equipment</p> <p>Large, easy to read backlight display automatically sets the correct measurement range so you do not need to change the switch positions while taking a measurement</p>	1	34,350.00

Section III- BID DATA SHEET – PROCUREMENT OF ELECTRICAL/ELECTRONICS EQUIPMENT

	<p>Electrical Specifications AC Current via Jaw; Range 374 and 375; 376 600.0 A 999.9 A; Resolution 0.1 A; Accuracy 2% ± 5 digits (10-100 Hz) 2.5% ± 5 digits (100-500 Hz); Crest Factor (50/60 Hz) 3 @ 500 A (375 and 376 only); 2.5 @ 600 A; 1.42 @1000 A (376 only) Add 2% for C.F. > 2 AC Current via Flexible Current Probe Range 2500 A Resolution 374 and 375 0.1 A (≤ 600 A); 1 A (≤ 2500A) 376 0.1 A (≤ 999.9 A);1 A (≤ 2500 A); Accuracy 3% ± 5 digits (5 – 500 Hz); Crest Factor (50/60Hz) 3.0 at 1100 A (375 and 376 only) 2.5 at 1400 A; 1.42 at 2500 A; Add 2% for C.F. > 2 DC Current Range 374 and 375; 376 600.0 A; 999.9 A Resolution 0.1 A; Accuracy 2% ± 5 digits; AC Voltage Range 374 and 375; 376 600.0 V; 1000 V Resolution 374 and 375; 376 0.1 V; 0.1 V (≤ 600.0 V) 1 V (≤ 1000 V); Accuracy 1.5% ± 5 digits (20 – 500 Hz) DC Voltage; Range 374 and 375; 376 600.0 V 1000 V; Resolution 374 and 375; 376 0.1 V 0.1 V (≤ 600.0 V); 1 V (≤ 1000 V); Accuracy 1% ± 5 digits</p>		
unit	<p>INSULATION TESTER General Specifications: Maximum voltage applied to any terminal: 600 V ac rms or dc Storage temperature: -40 °C to 60 °C (-40 °F to 140 °F) Operating temperature: -20 °C to 55 °C (-4 °F to 131 °F) Temperature coefficient: 0.05 x (specified accuracy) per °C for temperatures < 18 °C or > 28 °C (< 64 °F or > 82 °F) Relative humidity noncondensing: 0 % to 95 % @ 10 °C to 30 °C (50 °F to 86 °F) 0 % to 75 % @ 30 °C to 40 °C (86 °F to 104 °F) 0 % to 40 % @ 40 °C to 55 °C (104 °F to 131 °F) Vibration: Random, 2 g, 5-500 Hz per MIL-PRF-28800F, Class 2 instrument Shock: 1 meter drop per IEC 61010-1 2nd Edition (1 meter drop test, six sides, oak floor) Electromagnetic compatibility: In an RF field of 3 V/M, accuracy = specified accuracy (EN 61326-1:1997) Safety: Complies with ANSI/ISA 82.02.01 (61010-1) 2004, CAN/CSA-C22.2 NO. 61010-1-04, and IEC/EN 61010-1 2nd Edition for measurement category IV 600 V (CAT IV) Certifications: CSA per standard CSA/CAN C22.2 No. 61010.1-04; TUV per standard IEC/EN 61010-1 2nd Edition Batteries: Four AA batteries (NEDA 15A or IEC LR6) Battery life</p>	1	46,900.00

Section III- BID DATA SHEET – PROCUREMENT OF ELECTRICAL/ELECTRONICS EQUIPMENT

	<p>Insulation test use: Tester can perform at least 1000 insulation tests with fresh alkaline batteries at room temperature. These are standard tests of 1000 V into 1 MΩ with a duty cycle of 5 seconds on and 25 seconds off.</p> <p>Resistance measurements: Tester can perform at least 2500 earth bond resistance measurements with fresh alkaline batteries at room temperature. These are standard tests of 1 Ω with a duty cycle of 5 seconds on and 25 seconds off.</p> <p>Size: 5.0 cm H x 10.0 cm W x 20.3 cm L (1.97 in H x 3.94 in W x 8.00 in L)</p> <p>Weight: 550 g (1.2 lb)</p> <p>IP rating: IP40 Altitude, Operating: 2000 m CAT IV 600 V, 3000 m CAT III 600 V, Non-operating (storage): 12,000 m</p> <p>Over-range capability: 110 % of range</p> <p>Included accessories: TL224 Test Leads, TP74 Test Probes, clips PN 1958654 (red) and PN 1958646</p>		
unit	<p>IntelliTone™ Pro 200 LAN Toner, Tracer and Probe Kit</p> <p>GENERAL SPECS:</p> <p>Operating temperature: 32 °F to 104 °F (0 °C to 40 °C)</p> <p>Storage temperature: -4 °F to +140°F (-20 °C to °C)</p> <p>Operating relative humidity (% RH without condensation)</p> <p>95 % (50 °F to 95 °F; 10 °C to 35 °C)</p> <p>75 % (95 °F to 104 °F; 35 °C to 40 °C) Uncontrolled < 50 °F (< 10 °C)</p> <p>Vibration: Random, 2 g, 5 Hz-500 Hz</p> <p>Shock: 1 m drop test</p> <p>Safety: EN 61010-1, Category: None</p> <p>Altitude: 3000 m</p> <p>EMC: EN 61326-1, FCC Part 15 B</p> <p>Battery type and life : 9 V alkaline (NEDA 1604A or IEC 6LR61); 20 hours typical</p> <p>Applications:</p> <p>Copper cabling media including; 75 or 50 Ohm Coaxial cable; Two Conductor control, security, generic cabling. 10 Base-T or 10/100 Base-T datacom networks. UTP cable. Shielded Twisted Pair supported in Cablemap function of the IntelliTone 200.</p> <p>TONER SPECS</p> <p>Dimensions: 5.54 in x 2.94 in x 1.25 in (14.1 cm x 7.5 cm x 3.2 cm)</p> <p>Display: LED</p> <p>Control: Thumbwheel switch</p> <p>Toner interface:</p> <p>Main Mod8 port for tone generation on all 4 pairs of UTP / STP cabling. F Connector for coaxial cabling</p> <p>Banana Jack Plugs (2) - two conductor wiring</p> <p>Toner frequency: IntelliTone™ signal: encoded digital signal</p>	1	19,730.00

Section III- BID DATA SHEET – PROCUREMENT OF ELECTRICAL/ELECTRONICS EQUIPMENT

=====

	<p>Analog SmartTone signal: 500 - 1200Hz, 4 songs Output power: 5 V p-p Auto power down Turns off automatically after 2 1/2 hours of inactivity PROBE SPECS Dimensions; 8.73 in x 1.88 in x 1.26 in (22.2 cm x 4.8 cm x 3.2 cm) Display; (8) LED indicators, Sync LED indicator Audio: IntelliTone: Microprocessor controlled audio files Analog: Detected toner signal Control: Thumbwheel switch, volume control wheel Tone detection Detects IntelliTone™ digital signal for Locate, Isolate, and CableMap Detects analog SmartTone signal (500-1200Hz) and other analog toners. Toner interface Main Mod8 port for cablemap on all 4 pairs of UTP / STP cabling. Auto power down Turns off automatically after 1 hour of inactivity</p>		
	NOTE: ITEMIZED EVALUATION		
20.2	The Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the BDS.		
21.2	NOT APPLICABLE		